

TECHNICAL DATA SHEET

LB-1100

Natural-Based, Heavy-Duty Metalworking Lubricant

DESCRIPTION

LB-1100 is a premium heavy-duty metalworking lubricant with non-chlorinated extreme pressure additives. It is manufactured using renewable raw materials and is non-toxic and biodegradable. Ideal for machining exotic alloys common to the aerospace industry. Cleaning required before heat treating.

APPLICATIONS

- Heavy-duty operations
- Deep hole drilling
- Large diameter tapping
- Sawing large diameter solids
- Carbon die stamping

MATERIALS COMPATIBILITY

Recommended for ferrous and nonferrous metals

PHYSICAL PROPERTIES

Appearance	. Dark blue fluid
Specific Gravity	
Density	
Viscosity at 40°C	
Flash Point	
Pour Point	. 5°F (-15°C)
Pin & Vee Block	. 4500 lbs (maximum load capacity)
Sulfur	. None
Chlorine	. None
Silicones	. None
Mineral Oil	. 0%
Water Solubility	. Emulsifiable

AVAILABLE IN

1 gal L	_B1100
55 galL	B1155

HEALTH AND SAFETY

This product is made from renewable raw materials and is naturally non-toxic. For complete health and safety information refer to product MSDS (Material Safety Data Sheet) on our web site at www.rocolnorthamerica.com.

For additional information please contact our Customer Service Department at 800-452-5823 ext. 2.

Revision: July 31, 2008





