

LB-6800

Natural-Based, Moderate-Duty Metalworking Lubricant

DESCRIPTION

LB-6800 is a moderate-duty lubricant designed for aluminum sawing with superior lubricity and low odor. It is manufactured using renewable raw materials and is non-toxic and biodegradable. Cleaning not required before heat treating since LB-6800 is non-staining and burns off easily.

APPLICATIONS

- Moderate-duty operations
- Aluminum sawing and machining

MATERIALS COMPATIBILITY

- Recommended for aluminum, ferrous and nonferrous metals.

PHYSICAL PROPERTIES

<i>Appearance</i>	Purple viscous fluid
<i>Specific Gravity</i>	0.93
<i>Density</i>	7.8 lbs/gal (930 kg/m ³)
<i>Viscosity at 40°C</i>	9.0 cSt
<i>Flash Point</i>	400°F (204°C)
<i>Pour Point</i>	-40°F (-40°C)
<i>Pin & Vee Block</i>	4500 lbs (maximum load capacity)
<i>Sulfur</i>	None
<i>Chlorine</i>	None
<i>Silicones</i>	None
<i>VOCs</i>	Nil
<i>Mineral Oil</i>	0%
<i>Water Solubility</i>	Insoluble

AVAILABLE IN

1 gal.....	LB6800
55 gal.....	LB6855

HEALTH AND SAFETY

This product is made from renewable raw materials and is naturally non-toxic. For complete health and safety information refer to product MSDS (Material Safety Data Sheet) on our web site at www.rocolnorthamerica.com.

For additional information please contact our Customer Service Department at 800-452-5823 ext. 2.

Revision: July 31, 2008